2A MDM LOAD IN DIAGNOSTIC STATE (2A-3A)

1. <u>PERFORM PRE-LOAD SANITY CHECK WITH MEMORY MAP AND FILE TO BE LOADED</u>

FMT:LOAD:INITIATOR

If S/W Load

√SW_Load_XX_EEPROM_XX - (SW Load Version ID i.e. Rev 2)

√Memory Location - EEPROM

√SW_Load_EEPROM_Start_Addr - compatible with Memory Map

√SW_Load_XX_Wd_Count - compatible with Memory Map

If ADT Load

NOTE

Separate files are required for Loads to non-contiguous memory areas, and also for DRAM and EEPROM Loads.

√Memory Location - EEPROM

√ADPXX_EEPROM_Start_Addr - compatible with Memory Map

√ADPXX Wd Count - compatible with Memory Map

√ADPXX_Ver_Id -

√ADPXX Cksum -

√Destination_Device - MDMXX

2. <u>CONFIGURE FOR COMMAND UPLINK</u>

TELCOM: TBD

If N1-2 is Primary (N1-1 is in Diagnostics)

√Command Path-Orbiter/Early Comm

If uplink path = orbiter (Normal OIU configuration)

√OIU Routing Code -

Send Enable RT Device command to enable N1-1 MDM

 $\sqrt{N1-1}$ = Enable RT

Send Disable NCS Auto Retry on N1-1

 $\sqrt{N1-2}$ Auto Retry on N1-1 = Disable

If N1-1 is Primary (N1-2 is in Diagnostics)

√Command Path-Orbiter/Early Comm

If uplink path = orbiter

Reconfigure the OIU to RT on Bus 3, BC on Bus 4, and Format 002.

√OIU_Routing_Code -

Send Enable RT Device command to enable N1-2 MDM

 $\sqrt{N1-2}$ = Enable RT

Send Disable NCS Auto Retry on N1-2

 $\sqrt{N1-1}$ Auto Retry on N1-2 = Disable

If both MDMs are in Diagnostics (orbiter must present)
Uplink Path = OIU
Reconfigure the OIU to make bus 3/4 BC to the MDM being loaded and use format 002.

√OIU_Routing_Code -

3. SEND LOAD FILE

FMT:LOAD:INITIATOR

NOTE

Send all load cmd files. Multiple ADP files may be required.

cmd__SW_PT#_Uplink (TBD)
cmd_ADP_XX_cksum _Uplink (TBD)

4. VERIFY COMPLETION OF LOAD

FMT:LOAD:INITIATOR

√FMT_Load_Status - 100% complete

5. REINITIALIZE EEPROM

Perform SODF: REINITIALIZE NODE 1 MDMs procedure

08 MAY 98 1-23 ISS MAL/2A.1/PRE